

Material Safety Data Sheet

WHMIS (Pictograms)	WHMIS (Classification)	Protective Clothing	TDG (pictograms)
	Not controlled		\bigotimes

Section 1. Ch	Section 1. Chemical Product and Company Identification				
Product Name	HYDREX* AW 22, 32, 46, 68, 80, 100	Code	490-138, HDXAW22; 490-139, HDXAW32; 490-140, HDXAW46; 490-141, HDXAW68; 490-142, HDXAW80; 490-137, HDXAW10.		
Synonym	Not available	Validated o	n 12/12/2003.		
Manufacturer	PETRO-CANADA P.O. Box 2844 Calgary, Alberta T2P 3E3	<u>In case of</u> Emergency	Petro-Canada: 403-296-3000 Canutec Transportation: 613-996-6666 Poison Control Centre: Consult		
Material Uses	These products are designed for use as heavy duty hydraulic power transmission fluids and for lubrication where good anti-wear and anti-oxidation properties are required. They would typically be used in high-pressure hydraulic systems, machine tools, presses, compressors, pumps, gear sets, and centralized bearing lubrication systems.		local telephone directory for emergency number(s).		

				Exp	oosure Limits (ACGIH)	-
	Name	CAS #	% (V/V)	TLV-TWA(8 h)	STEL	CEILING
	nydrotreated and hydrocracked base er proprietary, non-hazardous	Mixture	100	5 mg/m³ (oil mist)	10 mg/m³ (oil mist)	Not established
Manufacturer Recommendation	Not applicable					
Other Exposure Limits	Consult local, state, provincial or territory authorities for acceptable exposure limits.					

Section 3. Hazards Identification.			
Potential Health Effects	Prolonged or repeated contact may cause skin irritation, defatting, drying and dermatitis. Not expected to cause more than slight skin or eye irritation. With its relatively low vapour pressure, this product is not expected be inhaled in any appreciable quantity at ambient conditions. If heated to high temperatures or subjected to mechanical actions which produce vapours or mists, inhalation may cause respiratory tract irritation. Ingestion may produce a laxative effect. For more information refer to Section 11 of this MSDS.		

Section 4. First Aid Measures			
Eye Contact	IMMEDIATELY flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek medical attention.		
Skin Contact	Remove contaminated clothing - launder before reuse. Wash gently and thoroughly the contaminated skin with running water and non-abrasive soap. Seek medical attention.		
Inhalation	Evacuate the victim to a safe area as soon as possible. If the victim is not breathing, perform artificial respiration. Allow the victim to rest in a well ventilated area. Seek medical attention.		
Ingestion	DO NOT induce vomiting because of danger of aspirating liquid into lungs. Seek medical attention.		
Note to Physician	Not available		

Section 5. Fire-fighting Measures				
Flammability	May be combustible at high temperature.	Flammable Limits	Not available	
Flash Points	OPEN CUP: ≥207°C (404.6°F) (Cleveland)	Auto-Ignition Temperature	Not available	
Fire Hazards in Presence of Various Substances	Low fire hazard. This material must be heated before ignition will occur.	Explosion Hazards in Presence of Various Substances	Do not cut, weld, heat, drill or pressurize empty container. Containers may explode in heat of fire.	

HYDREX* AW 22, 32	, 46, 68, 80, 100 Page Number: 2
Products of Combustion	Carbon oxides (CO, CO2), nitrogen oxides (NOx), sulphur oxides (SOx), smoke and irritating vapours as products of incomplete combustion.
Fire Fighting Media and Instructions	NAERG96, GUIDE 171, Substances (low to moderate hazard). If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (0.5 mile) in all directions; also, consider initial evacuation for 800 meters (0.5 mile) in all directions. Shut off fuel to fire if it is possible to do so without hazard. If this is impossible, withdraw from area and let fire burn out under controlled conditions. Withdraw immediately in case of rising sound from venting safety device or any discolouration of tank due to fire. Cool containing vessels with water spray in order to prevent pressure build-up, autoignition or explosion. SMALL FIRE: use DRY chemicals, foam, water spray or CO2. LARGE FIRE: use water spray, fog or foam. For small outdoor fires, portable fire extinguishers may be used, and self contained breathing apparatus (SCBA) may not be required. For all indoor fires and any significant outdoor fires, SCBA is required. Respiratory and eye protection are required for fire fighting personnel.

Section 6. Accidental Release Measures Material Release or Spill

Consult current National Emergency Response Guide Book (NAERG) for appropriate spill measures if necessary. Extinguish all ignition sources. Stop leak if safe to do so. Dike spilled material. Use appropriate inert absorbent material to absorb spilled product. Collect used absorbent for later disposal. Avoid contact with spilled material. Avoid contanting sewers, streams, rivers and other water courses with spilled material. Notify appropriate authorities immediately.

Section 7. H	Section 7. Handling and Storage			
Handling	Avoid contact with any sources of ignition, flames, heat, and sparks. Avoid eye contact. Avoid skin contact. Avoid inhalation of product vapours or mists. Empty containers may contain product residue. Do not pressurize, cut, heat, or weld empty containers. Do not reuse containers without commercial cleaning and/or reconditioning. Personnel who handle this material should practice good personal hygiene during and after handling to help prevent accidental ingestion of this product. Properly dispose of contaminated leather articles including shoes that cannot be decontaminated.			
Storage	Store away from incompatible and reactive materials (See section 5 and 10). Keep container tightly closed. Store in dry, cool, well-ventilated area.			

Section 8. Exposu	Section 8. Exposure Controls/Personal Protection			
Engineering Controls	For normal application, special ventilation is not necessary. If user's operations generate vapours or mist, use ventilation to keep exposure to airborne contaminants below the exposure limit. Make-up air should always be supplied to balance air removed by exhaust ventilation. Ensure that eyewash station and safety shower are close to work-station.			
	- The selection of personal protective equipment varies, depending upon conditions of use. Eye protection (i.e., safety glasses, safety goggles and/or face shield) should be determined based on conditions of use. If product is used in an application where splashing may occur, the use of safety goggles and/or a face shield should be considered.			
Body	Wear appropriate clothing to prevent skin contact. As a minimum long sleeves and trousers should be worn.			
Respiratory	Where concentrations in air may exceed the occupational exposure limits given in Section 2 (and those applicable to your area) and where engineering, work practices or other means of exposure reduction are not adequate, NIOSH approved respirators may be necessary to prevent overexposure by inhalation.			
Hands	Wear appropriate chemically protective gloves. When handling hot product ensure gloves are heat resistant and insulated.			
East	Wear appropriate features to provent product from coming in contact with feat and skin			

Feet Wear appropriate footwear to prevent product from coming in contact with feet and skin.

Physical State and Appearance	Viscous liquid.	Viscosity	22: 21.59 cSt @ 40°C, 4.26 cSt @ 100°C VI=101 32: 34.5 cSt @ 40°C, 5.68 cSt @ 100°C VI=103 46: 46.6 cSt @ 40°C, 6.94 cSt @ 100°C VI=105 68: 65.7 cSt @ 40°C, 8.51 cSt @ 100°C, VI=99 80: 80.0 cSt @ 40°C, 9.71 cSt @ 100°C, VI=99 100: 100 cSt @ 40°C, 11.32 cSt @ 100°C VI=99
Colour	Pale, straw-yellow.	Pour Point	22: -45°C (-49°F) 32: -39°C (-38°F) 46: -33°C (-27°F) 68: -33°C (-27°F) 80: -24°C (-11°F) 100: -30°C (-22°F)
Odour	Mild petroleum oil like.	Softening Point	Not applicable.
Odour Threshold	Not available	Dropping Point	Not applicable.
Boiling Point	Not available	Penetration	Not applicable.
Density	0.8587 - 0.8728 kg/L @ 15ºC (59ºF).	Oil / Water Dist. Coefficient	Not available

HYDREX* AW 22, 32, 4	6, 68, 80, 100		Page Number: 3
Vapour Density	Not available	Ionicity (in water)	Not available
Vapour Pressure	Negligible at ambient temperature and pressure.	Dispersion Properties	Not available
Volatility	Non-volatile.	Solubility	Insoluble in water.

Section 10. Stabil	Section 10. Stability and Reactivity				
Corrosivity	Copper corrosion, 3h, 100°C (ASTM D0130): 1a				
Stability	The product is stable under normal handling and storage conditions.	Hazardous Polymerization	Will not occur under normal working conditions.		
Incompatible Substances / Conditions to Avoid	Reactive with oxidizing agents and acids.	Decomposition Products	May release COx, SOx, H2S, POx, CaOx, ZnOx, methacrylate monomers, aldehydes, alkyl mercaptans, smoke and irritating vapours when heated to decomposition.		

Routes of Entry	Skin contact, eye contact, inhalation and ingestion.
Acute Lethality	Acute toxicity information is not available for the product as a whole, therefore, data for some of the ingredients is provided below: Acute Oral toxicity (LD50): >5000 mg/kg (rat) Acute Dermal toxicity (LD50): >2000 mg/kg (rabbit) Acute Inhalation toxicity (LC50): >2500 mg/m ³ /4h (rat)
Chronic or Other Toxic Effects Dermal Route:	Prolonged or repeated contact may defat and dry skin, and cause dermatitis. Short-term exposure is expected to cause only slight irritation, if any.
Inhalation Route:	With its relatively low vapour pressure, this product is not expected be inhaled in any appreciable quantity a ambient conditions. If heated to high temperatures or subjected to mechanical actions which produce vapours or mists, inhalation may cause respiratory tract irritation.
Oral Route:	Ingestion of this product may lead to aspiration of the liquid, especially if vomiting occurs. This may result in chemical pneumonitis (inflammation of the lungs) and/or pulmonary edema (an accumulation of fluid in the lungs). May produce a laxative effect.
Eye Irritation/Inflammation:	Short-term exposure is expected to cause only slight irritation, if any.
Immunotoxicity:	Not available
Skin Sensitization:	Contact with this product is not expected to cause skin sensitization, based upon the available data and the known hazards of the components.
Respiratory Tract Sensitization:	Contact with this product is not expected to cause respiratory tract sensitization, based upon the available data and the known hazards of the components.
Mutagenic:	This product is not known to contain any components at >= 0.1% that have been shown to cause mutagenicity. Therefore, based upon the available data and the known hazards of the components, this product is not expected to be a mutagen.
Reproductive Toxicity:	This product is not known to contain any components at >= 0.1% that have been shown to cause reproductive toxicity. Therefore, based upon the available data and the known hazards of the components, this product is not expected to be a reproductive toxin.
Teratogenicity/Embryotoxicity:	This product is not known to contain any components at >= 0.1% that have been shown to cause teratogenicity and/or embryotoxicity. Therefore, based upon the available data and the known hazards of the components, this product is not expected to be a teratogen/embryotoxin.
Carcinogenicity (ACGIH):	This product is not known to contain any chemicals at reportable quantities that are listed as Group A1 or A2 carcinogens by ACGIH.
Carcinogenicity (IARC):	This product is not known to contain any chemicals at reportable quantities that are listed as Group 1, 2A, o 2B carcinogens by IARC.
Carcinogenicity (NTP):	This product is not known to contain any chemicals at reportable quantities that are listed as carcinogens by NTP.
Carcinogenicity (IRIS):	This product is not known to contain any chemicals at reportable quantities that are listed as carcinogens by IRIS.
Carcinogenicity (OSHA):	This product is not known to contain any chemicals at reportable quantities that are listed as carcinogens by OSHA.
Other Considerations	No additional remark.

HYDREX* AW 22, 32, 46, 68, 80, 100

Section 12. Ecological Information				
Environmental Fate	Not available	Persistance/ Bioaccumulation Potential	Not available	
BOD5 and COD	Not available	Products of Biodegradation	Not available	
Additional Remark	ks No additional remark.			

 Section 13. Disposal Considerations

 Waste Disposal
 Spent/ used/ waste product may meet the requirements of a hazardous waste. Consult your local or regional authorities. Ensure that waste management processes are in compliance with government requirements and local disposal regulations.

Section 14. Trans	sport Information				
TDG Classification	Not a hazardous material for transport according to the TDG Regulations. (Canada)	Special Provisions for Transport	Not applicable.		
Section 15. Regu	latory Information				
Other Regulations	This product is acceptable for use under the provisions of WHMIS-CPR. All components of this formulation are listed the CEPA-DSL (Domestic Substances List).				
	All components of this formulation are listed on the US EPA-TSCA Inventory.				
	All components of this formulation are listed on EINECS or are exempt. 32, 46, 68: German Water Hazard Classification (Verwaltungsvorschrift wassergefährdende Stoffe - VwVwS) WGK=1 This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.				
	Please contact Product Safety for more inform	ation.			
DSD/DPD (Europe)	Not classified under the Dangerous Substances or Dangerous Preparations Directives.		Does not meet the definitions of a health or physical hazard according to the OSHA - Hazard Communication Standard. (United States)		
ADR (Europe) (Pictograms)		DOT (U.S.A) (Pictograms)	\bigotimes		
HMIS (U.S.A.)	Health Hazard 1 NFPA (U.	S.A.) Fire H			
	Fire Hazard	Health 1 0 Rea	1 Slight 2 Moderate		
	Reactivity 0	Speci	ific hazard 3 High		
	Personal Protection B		4 Extreme		

Section 16. Other Information					
References Available upon request. * Marque de commerce de Petro-Canada - Trade	Available upon request. * Marque de commerce de Petro-Canada - Trademark				
Glossary ACGIH - American Conference of Governmental Industrial Hygienists ADR - Agreement on Dangerous goods by Road (Europe) ASTM - American Society for Testing and Materials (BOD5 - Biological Oxygen Demand in 5 days CAN/CGA B149.2 Propane Installation Code CAS - Chemical Abstract Services CEPA - Canadian Environmental Protection Act CERCLA - Comprehensive Environmental Response, Compensation and Liability Act CFR - Code of Federal Regulations CHIP - Chemical SHazard Information and Packaging Approved Supply List COD5 - Chemical Oxygen Demand in 5 days CPR - Controlled Products Regulations DOT - Department of Transport DSCL - Dangerous Substances Classification and Labeling (Europe) DSI/DPD - Dangerous Substances or Dangerous Preparations Directives (Europe) DSL - Domestic Substance List EEC/EU - European Economic Community/European Union EINECS - European Inventory of Existing Commercial Chemical Substances EPCRA - Federal Insecticide, Fungicide and Rodenticide Act	IRIS - Integrated Risk Information System LD50/LC50 - Lethal Dose/Concentration kill 50% LDLo/LCL0 - Lowest Published Lethal Dose/Concentration NAERG'96 - North American Emergency Response Guide Book (1996) NFPA - National Fire Prevention Association NIOSH - National Institute for Occupational Safety & Health NPRI - National Institute for Occupational Safety & Health NPRI - National Pollutant Release Inventory NSNR - New Substances Notification Regulations (Canada) NTP - National Toxicology Program OSHA - Occupational Safety & Health Administration PEL - Permissible Exposure Limit RCRA - Resource Conservation and Recovery Act SARA - Superfund Amendments and Recorey Act SARA - Superfund Amendments and Recorey Act SD - Single Dose STEL - Short Term Exposure Limit (15 minutes) TDG - Transportation Dangerous Goods (Canada) TDLo/TCL0 - Lowest Published Toxic Dose/Concentration TLm - Median Tolerance Limit TLV-TWA - Threshold Limit Value-Time Weighted Average TSCA - Toxic Substances Control Act USEPA - United States Environmental Protection Agency USP - United States Pharmacopoeia WHMIS - Workplace Hazardous Material Information System				
Continued on Next Page Internet: www.petro-canada.ca/msds					

HYDREX* AW 22, 32, 46, 68, 80, 100	Page Number: 5
HCS - Hazardous Communication System HMIS - Hazardous Material Information System IARC - International Agency for Research on Cancer	
For Copy of MSDS	Prepared by Product Safety - JDW on 12/12/2003.
The Canadian Controlled Products Regulations (CPR) (Under the Hazardous Products Act, part of the WHMIS legislation) only apply to WHMIS Controlled (i.e., hazardous) products. Therefore, the CPR and the 3-year update rule specified therein do not apply to WHMIS Non-Controlled products. Although this is true, customarily Petro-Canada reviews and updates Non-Controlled product MSDS if a customer requests such an update. These Non-Controlled product updates are given a lower priority than Controlled products but are handled as soon as practicable. If you would like to verify if the MSDS you have is the most current, or you require any further information, please contact:	Data entry by Product Safety - JDW.
Internet: www.petro-canada.ca/msds	
Lubricants: Western Canada, telephone: 1-800-661-1199; fax: (780) 464-9564 Ontario & Central Canada, telephone: 1-800-268-5850 and (905) 822-4222; fax: 1-800-201-6285 Quebec & Eastern Canada, telephone: 1-800-576-1686; fax: 800-201-6285	
For Product Safety Information: (905) 804-4752	

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.