

MODEL P-6036 SCISSORS LIFT - LIFT TABLE

10 Year/250,000 Cycle Warranty

The P-Series lifts are our most popular series as they fit a wide array of manufacturing applications.

**ISO 9001:2008
Certified**



Min. Platform Size: 24 x 48 in.

Max. Platform Size: 48 x 72 in.

Max. End Load Capacity: 4,100 lbs.

Max. Side Load Capacity: 3,500 lbs.

Baseframe Size: 24 x 48 in.

Lowered Height: 6.5 in.

Raised Height: 42.5 in.

Approx. Speed Up: 23 sec.

Internal Motor: 2 HP

Shipping Weight: 680 lbs.




6,000 lb. Capacity - 36 in. Travel

SPECIAL FEATURES & BENEFITS


- ▶ These units are equipped with the patented "Platform Centering Devices", which doubles or triples lift life.
- ▶ All of the controllers are Underwriter Laboratory listed assemblies.
- ▶ These units are fully primed and finished with a baked enamel finish.
- ▶ The cylinders are machine grade with clear plastic return lines.
- ▶ All pressure hoses are double wire braid with JIC fittings.
- ▶ The reservoirs are mild steel.
- ▶ These units conform to all applicable ANSI codes.

CLICK HERE FOR: [Optional Accessories](#)

FEATURE DETAILS




▶ **Platform Centering
Device**



▶ **Machine
Grade Cylinder**



▶ **Double Wire
Braid Hose**



▶ **Power Unit**