

## MODEL 612810 TOP OF GROUND DOCK LIFT

## 2 Year Parts & Labor/10 Year Structural Warranty

These are Instant Docks that simply require lagging into position and plugging into a power receptacle and they are ready to go to work. No pit work is required.







Axle Capacity Ends: 9,600 lbs.
Platform Size: 8 x 10 ft.
Overall Size w/Ramp: 110 x 180 in.
Lowered Height: 6 in.
Bridge Size: 18 x 72 in.
Ramp Size: 42 x 84 in.
7.5 HP Motor
Approx. 10 FPM

Capacity: 12,000 lbs.

Shipping Weight: 5,455 lbs.

52" Travel



## **SPECIAL FEATURES & BENEFITS**

- All models are equipped with a hinged bridge equipped with a pull back chain.
- All models have an approach ramp.
- ▶ All of the electrical controllers are Underwriters Laboratories approved assemblies.
- Each unit is washed with phosphoric acid, fully primed and then finished with baked enamel.
- All cylinders are machine grade with clear plastic return lines.
- All pressure hoses are double wire braid with JIC fittings.
- ▶ These units conform to all applicable ANSI codes.

CLICK HERE FOR: Drawing Pad Diagram Specifications Optional Accessories

## FEATURE DETAILS




► Power Unit w/Controller



► UL Listed Control
Panel



Double Wire Braid Hose



Combination Wheel Chock/Ramp



Phone: 800-843-3625 • Fax: 630-584-9405 • www.advancelifts.com