

MODEL 68710 TOP OF GROUND DOCK LIFT

2 Year Parts & Labor/10 Year Structural Warranty

These are Instant Docks that simply require lagging into position and plugging into a power receptacle and they are ready to go to work. No pit work is required.



Capacity: 8,000 lbs. Axle Capacity Ends: 6,400 lbs. Platform Size: 7 x 10 ft. Overall Size w/Ramp: 98 x 180 in. Lowered Height: 6 in. Bridge Size: 18 x 66 in. Ramp Size: 42 x 72 in. 5 HP Motor Approx. 11 FPM 52" Travel Shipping Weight: 4,795 lbs.



SPECIAL FEATURES & BENEFITS

- All models are equipped with a hinged bridge equipped with a pull back chain.
- All models have an approach ramp.
- > All of the electrical controllers are Underwriters Laboratories approved assemblies.
- **Each unit is washed with phosphoric acid, fully primed and then finished with baked enamel.**
- > All cylinders are machine grade with clear plastic return lines.
- All pressure hoses are double wire braid with JIC fittings.
- These units conform to all applicable ANSI codes.

CLICK HERE FOR: Dra

Drawing

Specifications

Optional Accessories

FEATURE DETAILS



Power Unit w/Controller



Pad Diagram

UL Listed Control Panel



Double Wire Braid Hose



Combination Wheel Chock/Ramp



Phone: 800-843-3625 • Fax: 630-584-9405 • www.advancelifts.com