



Loading Dock Sectional Doors

Loading Dock Solutions

Raynor Garage Doors has a number of solutions to complement any dock position needing a sectional overhead door. Choose from a variety of styles including, Pan Doors, Pan Doors with Insulation, and Steel Two Sided Sectional doors. All models in the program are available in stock sizes covering the most common opening sizes and feature heavy duty Raynor hardware including diamond hinges and full angle mount hardware.



Heavy Duty Hardware

Featuring heavy duty hardware engineered to exacting Raynor standards to handle high traffic loading dock areas.



Quick Shipping

Quick shipping with stock program for Dock door positions gets the door you need quickly.



Security

Raynor Garage Doors utilize high quality components and durable steel gauges in every door. Posi-Lock spring loaded locking mechanism ensures lock doors stay locked.

Choose the Door That Meets Your Application

Stock Program											
Series Model	Opening Width	Opening Height	Construction	Insulation (R-Value)	Surface Texture	Section Thickness	Exterior Steel Thickness	End/Center Stile Steel Thickness	Section Joint	Exterior Colors	Section Limited Warranty
DDS24C	8', 9', 10'	8', 9', 10'	Steel Pan	N/A	Smooth (Ribbed)	2"	24-Gauge Nominal	16-Gauge	Tongue & Groove	White	10-Year (Rust-through)
DDS24	8', 9', 10'	8', 9', 10'	Steel Pan with Insulation	Polystyrene (7.70)	Smooth (Ribbed)	2"	24-Gauge	16-Gauge	Tongue & Groove	White	10-Year (Rust-through)
DDTC200	8', 9', 10'	8', 9', 10'	Steel Two Sided	Expanded Polystyrene (10.25)	Stucco	2"	26-Gauge 26-Gauge	18-Gauge	Ship Lap	White	10-Year (Rust-through and Delamination)

*Additional sizes, colors and options available.

**All doors come standard with 2" vertical lift angle mounted track

Security and Durability



Diamond Hinges


Raynor Diamond Hinges add an additional vertical fastening point to the hardware fastening system. This additional fastening point spreads the load across the diamond hinge providing increased strength and durability. Diamond hinges are standard for all Raynor edge and center hinges.



Spring Loaded Lock

Spring loaded slide lock ensures that entry cannot be gained when door panel is flexed. Doors are safely locked with the 6" long heavy duty lock bar. With spring loaded construction and 1/4" thick slide, the lock is designed for security and durability.

Raynor Commercial Operators



ControlHoist™ Standard

Rated for 30 cycles per hour, choose the belt-drive ControlHoist STANDARD operator, ideal for standard to larger size sectional and rolling doors. Available in trolley or jackshaft, with or without a hoist, in 1/3 and 1/2 horsepower units, at 115/230 volt single phase or 230/460 volt three phase.



ControlHoist™ Basic

Rated for 10 cycles per hour, ControlHoist BASIC belt-drive operators are perfect for operating smaller-sized sectional or rolling steel doors. Still loaded with easy-to-set features, this 1/2 horsepower unit is perfect for most commercial applications. 115/230 volt.